

Fir Tree Cable Ties

Fir Tree Cable Ties

Fir Tree Cable Ties are recommended when an application requires one step fastening. The push mount portion of the cable tie is found outside the head of the tie and is pushed into a pre-drilled hole and locks into place. Fir Tree Cable Ties provide a constant tension and enables a stable and secure fixture. The one piece construction with a push mount feature outside the head of the tie allows for consistent performance and reliability. UV Black is recommended for outdoor applications, providing greater resistance to ultraviolet light.



Material: Nylon Polyamide 6.6 High Impact
modified UV and Heat Stabilized (PA66HIRHSUV)

Flammability: UL94V-HB

Temperature Range: -40 °F to 230 °F (-40 °C to +110 °C)

Part Number	Tensile	Length	Width	Thickness	Bundle Diameter	Hole Diameter	Bag Qty	Case Qty
L-8-50-FTPM	50 LB	8.6"	0.18	0.055	2"	.245 min .278 max	1,000	5,000

* Color → Heat Stabilized UV Black

Fir Tree Cable Tie Material Information	
Material	Nylon Polyamide 6.6 High Impact modified UV and Heat Stabilized (PA66HIRHSUV)
Flammability	UL94V-HB
Temperature Range	-40 °F to +230 °F (-40 °C to +110 °C)